



FIG. 1



2/8

FIG. 2



3/8

FIG. 3





FIG. 4



5/8

CIRCUMFERENCE  
CORRECTION VALUE

**EDGING ADJUSTMENT**

EDGING SIZE x 1000

31	100007	<input type="radio"/> ROUGH
32	0	<input type="radio"/> BEVEL (metal)
33	20	<input type="radio"/> BEVEL (plastic)
34	45	<input type="radio"/> FLAT
35	848	<input type="radio"/> FLAT POLISH
36	848	<input type="radio"/> BEVEL POLISH

FIG. 5


"891242,E1,02,286,281,02/05/20,16:06:45"  
"888866,E1,02,281,276,02/05/20,16:16:23"

TRAY NUMBER	EDGING UNIT MACHINE NUMBER	EDGING CONDITION	PRE-RENEWAL CIRCUMFERENCE CORRECTION VALUE	POST-RENEWAL CIRCUMFERENCE CORRECTION VALUE	RENEWAL DATE
----------------	-------------------------------------	---------------------	--	---	--------------

FIG. 6


6/8

FIG. 7



7/8

FIG. 8



EDGING CONDITION NO.1: A1 AND B1 AND C1

EDGING CONDITION NO.2: A1 AND B1 AND C2

EDGING CONDITION NO.3: A1 AND B1 AND C3

•  
•

EDGING CONDITION NO.X: A2 AND B2 AND C1

•  
•  
•

EDGING CONDITION NO.18: A3 AND B3 AND C3

